



group of companies

Preferred Powered Access provider to Nixon

needs, ensure every machine is maintained to the highest standard and delivered to site on time.

• 6,000 machines at 21 depots across the UK

Our team of skilled professionals will help you select the best access platform for your specific

- Working heights ranging from 3.6m to 58.6m
- Fast delivery using our own transport fleet
- 24 hour and 48 hour delivery option

Keeping you in control of your account at the click of a button. View your account in real time, online 24 hours a day, 365 days per year.



T: 0333 005 0003 E: enquiries@nixonextra.co.uk

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification.

MACHINE SPECIFICATION SHEET

BA63BS 20.80m

REACH HEIGHT	20.80m	PLATFORM HEIGHT	18.80m
CLOSED LENGTH	6.70m	CLOSED HEIGHT	2.15m
CLOSED WIDTH	2.27m	HORIZONTAL REACH	12.80m
LIFTING CAPACITY	225kg	WEIGHT	6,660kg
CAGE DIMENSIONS	0.85×1.80m	TURNING RADIUS	4.00m
ROTATION	360°	IPAF CATEGORY	3b
POWER	BI-ENERGY		

FEATURED MODEL NIFTYLIFT HR21BIS

