

EZiCAT i500	
Frequency / Mode	Power mode 50 Hz or 60 Hz, Radio mode 15 kHz to 60 kHz Generator mode 8 kHz and 33 kHz, Auto mode = Power + Radio mode
Depth	Power to 3m, Radio to 2m, Generator mode to 3m
Protection	Conforms to IP54
Bluetooth	Available
Batteries	6 x AA alkaline (IEC LR6 supplied)
Battery life	40 hours intermittent use (at 20°C)
Weight	2.7kg including batteries

EZiCAT i550	
Frequency / Mode	Power mode 50 Hz or 60 Hz, Radio mode 15 kHz to 60 kHz Generator mode 8 kHz and 33 kHz, Auto mode = Power + Radio mode
Depth	Power to 3m, Radio to 2m, Generator mode to 3m
Depth estimation	10% of depth in line or sonde (0.3 to 3m depth range)
Protection	Conforms to IP54
Bluetooth	Available
Batteries	6 x AA alkaline (IEC LR6 supplied)
Battery life	40 hours intermittent use (at 20°C)
Weight	2.7kg including batteries

EZiTRACE	
Frequency / Mode	8 kHz or 33 kHz, Constant dual frequency available in connection mode
Tracing range	Induction typically 150m, connection typically 250m
Protection	Conforms to IP67 (with lid closed)
Included accessories	Crocodile equipped connection cable set with earth spike
Batteries	4 x C alkaline (IEC LR14 supplied)
Battery life	40 hours continuous use
Weight	2.95kg including standard accessories and batteries

EZiROD	
Protection	Conforms to IP54 (30/50/80 metre coil of copper conductor sheated by fibre glass)
Included accessories	Connections to EZiTRACE cable set
Weight	3kg/3.25kg/3.5kg

Dealer stamp:

EZiSYSTEM

Advanced buried service location technology

NEW
i-Series
Locators

